BUR920020023US1

Amendments to the Claims

Amend claims 1, 4-5, 7, 10, and 16 as follows:

 (Currently Amended) A computerized simulation system for simulating an integrated circuit, wherein the simulation system uses a black box circuit model of the integrated circuit such that the integrated circuit details are hidden from a user, comprising:

a simulator module comprising an API wherein said API comprises at least one function and wherein said simulator module uses said function to define a component of the black box first circuit and its corresponding simulated behavior; and wherein said function is recorded as a recorded function and said recorded function, when called during a simulation, reproduces a behavior corresponding to the black box circuit;

a code module which is created by a program compiler, which compiles comprises a compilation of said-a plurality of recorded functions to form the code module, wherein the code module makes calls to the simulator module during simulation of the black box circuit; and

an interface between said code module and a user program wherein a user defines said code module inputs, outputs, and load parameters, and wherein the user is prevented from supplying inputs, output, and load parameters directly to the simulator module.

- 2. (Canceled)
- 3. (Canceled)
- 4. (Currently Amended) The <u>computerized simulation</u> system of claim 1, wherein the <u>interface</u> <u>between the user program and a circuit parameter is applied to said code module, wherein said parameter is provided through said user program by includes a static load model.</u>
- 5. (Currently Amended) The computerized simulation system of claim 1, wherein the interface

BUR920020023US1

between the user program and a circuit parameter is applied to said code module, wherein said parameter is provided through said user program by includes a dynamic callback function which defines the load parameters.

6. (Canceled)

7. (Currently Amended) The <u>computerized simulation</u> system of claim 1, wherein said code module is compiled into a library.

8. (Previously Presented) The system of claim 7, wherein said code module further comprises a dynamically loadable library having at least one instantiation of said function.

9. (Canceled)

10. (Currently Amended) A method of modeling an integrated circuit as a black box circuit so that the integrated circuit details remain hidden then simulating the integrated circuit using the black box circuit model comprising the steps of:

providing a simulator module comprising an API having at least one a plurality of functions function;

defining a first black box circuit by executing said functions;

recording a plurality of said functions used by said simulator module during said step of defining said first black box circuit to create a plurality of recorded functions;

compiling said recorded functions together to create a circuit code module, wherein the code module makes calls to the simulator module during operation;

adding an interface to said code module which provides access to said code module from a user program;

linking said compiled code module to a circuit simulator; and

Docket No. BUR920020023US1 SN: 10/063,142 assigning inputs, outputs and load parameters to said code module by calling said code module through said interface: and;

simulating the integrated circuit using the black box model of the integrated circuit.

11. (Canceled)

- 12. (Previously Presented) The method of claim 10, further comprising the step of compiling said recorded functions into a library.
- 13. (Previously Presented) The method of claim 10, wherein said step of assigning said parameters to said code module comprises the step of providing a call-back function.
- 14. (Canceled)
- 15. (Canceled)
- 16. (Currently amended) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for modeling an integrated circuit as a black box circuit such that the integrated circuit details remain hidden from a user during simulation; and then simulating a using a simulator to model an IC, the method steps comprising:

providing a simulator module comprising an API having at least one a plurality of functions function:

defining a first black box circuit by executing said plurality of functions;

recording a plurality of said <u>plurality of functions</u> into a plurality of recorded functions used by said simulator module during said step of defining said first black box circuit;

compiling said recorded functions to create a code module, wherein the code module makes calls to the simulator module during simulation;

adding an interface to said code module which provides access to said code module from a user program;

linking said compiled code module to a circuit simulator; and

assigning inputs, outputs and load parameters to said code module by calling said circuit code module through said interface; and;

simulating the integrated circuit using the black box model of the integrated circuit.

simulating the integrated circuit using the black box model of the integrated circuit,
17. (Canceled)
18. (Previously Presented) The program storage device of claim 16, wherein the method steps further comprise the step of compiling said recorded functions into a library.
19. (Previously Presented) The program storage device of claim 16, wherein said step of assigning said parameters to said code module comprises the step of providing a call-back function.
20. (Canceled)
21. (Withdrawn)
22. (Withdrawn)
23. (Withdrawn)
24. (Withdrawn)
25. (Withdrawn)
26. (Withdrawn)
27. (Withdrawn)